

NAME: SINGLE SCREW FILM BLOWING MACHINE

参数及规格 PARAMETERS



Use: It is used for blowing the plastic laminated film of low density polyethylene (LDPE), high density polyethylene (HDPE) and linear low density polyethylene (LLDPE) etc., which are widely used for packing liquid, printed base material, products for export and industrial products, etc.

Main Technical Parameter				
Model 型号	TW-50	TW-55	TW-60	TW-65
Max. width 最大膜宽	600mm	800mm	1000mm	1200mm
Raw Material 使用材料	HDPE, LDPE, LLDPE, MLDPE			
Thickness 薄膜厚度	0.008-0.15MM			
Screw dia. 螺杆直径	Φ50	Φ55	Φ60	Φ65
Max. Capacity 最大产量	35kg/hr	55kg/hr	65kg/hr	80kg/hr
Main Motor Power 电机功率	11kw	15kw	18.5kw	22kw
Gear-box 齿轮箱	133	146	173	180
Die head type 膜头类型	ONE LAYER EXTRUDING			
Die head Size 膜头尺寸	Φ50/100	Φ100/150	Φ80/200	Φ100/220
Machine Dimension 设备尺寸	5*2.2*3.8m	5*2.4**4.0m	6.5*2.3*4.5m	6.5*2.5*5.0m

NAME: HIGH SPEED FILM BLOWING MACHINE

参数及规格 PARAMETERS



Use: It is used for blowing the plastic laminated film of low density polyethylene (LDPE), high density polyethylene (HDPE) and linear low density polyethylene (LLDPE) etc., which are widely used for packing liquid, printed base material, products for export and industrial products, etc.

Main Technical Parameter

Main Technical Parameter				
Model 型号	TW-H50	TW-H55	TW-H60	TW-H65
Max. width 最大膜宽	600mm	800mm	1000mm	1200mm
Raw Material 使用材料	HDPE, LDPE, LLDPE, MLDPE			
Thickness 薄膜厚度	0.008-0.15MM			
Screw dia. 螺杆直径	Φ50	Φ55	Φ60	Φ65
Max. Capacity 最大产量	55kg/hr	65kg/hr	75kg/hr	85kg/hr
Main Motor Power 电机功率	15kw	18.5kw	22kw	30kw
Gear-box 齿轮箱	146	173	173	180
Die head type 膜头类型	ONE LAYER EXTRUDING			
Die head Size 膜头尺寸	Φ60	Φ80	Φ100	Φ120
Machine Dimension 设备尺寸	4x2.5x4.5m	4.5x2.8x5.0m	5x3x5.2m	5.5x3.5x5.5m

NAME: ABA FILM BLOWING MACHINE



Characteristics:

1. ABA co-extrusion laminated film can prolong the length for preservation of liquid package.
2. The cylinder and the screw stem of the extruder are made of high quality alloy steel with optimum hardness and durable service after precision finishing and nitrogen treatment.
3. The auxiliary machine has a platform working table for making operation easy and is equipped with bubble stabilizing ring.
4. Double-rolling and double-cutting coiling unit adopts torque motor to keep proper tensions and make rolling even and roll- changing easy.

参数及规格 PARAMETERS

Main Technical Parameter			
Model 型号	2TW-55	2TW-60	2TW-70
Max. width 最大膜宽	500-1000mm	700-1200mm	800-1500mm
Raw Material 使用材料	HDPE, LDPE, LLDPE, MLDPE		
Thickness 薄膜厚度	0.05-0.15MM		
Screw dia. 螺杆直径	Φ50*2	Φ65*2	Φ65*2
Max. Capacity 最大产量	90kg/hr	110kg/hr	130kg/hr
Motor Power 电机功率	15kw*2	18.5kw*2	22kw*2
Tempt. Zone in extruding unit 温控区	3	3	4
Die head type 膜头类型	ABA CO-EXTRUDING		
Die head Size 膜头尺寸	Φ200	Φ250	Φ300
Machine Dimension 设备尺寸	6.5*2.1*5.3m	7*2.3*6.5m	7.2*2.5*7.2m

NAME: AB FILM BLOWING MACHINE



Characteristics:

1. AB co-extrusion laminated film can prolong the length for preservation of liquid package.
2. The cylinder and the screw stem of the extruder are made of high quality alloy steel with optimum hardness and durable service after precision finishing and nitrogen treatment.
3. The auxiliary machine has a platform working table for making operation easy and is equipped with bubble stabilizing ring.
4. Double-rolling and double-cutting coiling unit adopts torque motor to keep proper tensions and make rolling even and roll- changing easy.

参数及规格 PARAMETERS

Main Technical Parameter			
Model 型号	2TW-55	2TW-60	2TW-70
Max. width 最大膜宽	500-1000mm	700-1200mm	800-1500mm
Raw Material 使用材料	HDPE, LDPE, LLDPE, MLDPE		
Thickness 薄膜厚度	0.05-0.15MM		
Screw dia. 螺杆直径	Φ50*2	Φ65*2	Φ65*2
Max. Capacity 最大产量	90kg/hr	110kg/hr	130kg/hr
Motor Power 电机功率	15kw*2	18.5kw*2	22kw*2
Tempt. Zone in extruding unit 温控区	3	3	4
Die head type 膜头类型	AB CO-EXTRUDING		
Die head Size 膜头尺寸	Φ200	Φ250	Φ300
Machine Dimension 设备尺寸	6.5*2.1*5.3m	7*2.3*6.5m	7.2*2.5*7.2m

NAME: ABC FILM BLOWING MACHINE



Characteristics

1. ABC co-extrusion laminated film can prolong the length for preservation of liquid package.
2. The cylinder and the screw stem of the extruder are made of high quality alloy steel with optimum hardness and durable service after precision finishing and nitrogen treatment.
3. The auxiliary machine has a platform working table for making operation easy and is equipped with bubble stabilizing ring.
4. Double-rolling and double-cutting coiling unit adopts torque motor to keep proper tensions and make rolling even and roll- changing easy.

参数及规格 PARAMETERS

Main Technical Parameter			
Model 型号	3TW-1600	3TW-2000	3TW-2600
Max. width 最大膜宽	1000-1400mm	1400-1800mm	1800-2400mm
Raw Material 使用材料	HDPE, LDPE, LLDPE, MLDPE		
Thickness 薄膜厚度	0.03-0.15MM		
Screw dia. 螺杆直径	Φ50/60/55	Φ60/65/60	Φ65/70/65
Max. Capacity 最大产量	130kg/hr	180kg/hr	230kg/hr
Motor Power 电机功率	15/18.5/15 kw	18.5/22/18.5 kw	22/30/22 kw
Power consumption 耗电量	70kw	90kw	120kw
Die head type 膜头类型	ABC CO-EXTRUDING		
Die head Size 膜头尺寸	Φ350	Φ450	Φ600
Machine Dimension 设备尺寸	6.5*2.9*8.8m	7.5*3.4*9.8m	7.8*4.2*12.8m

NAME: PP FILM BLOWING MACHINE

Use: The PP film blowing machine is specially designed for the production of PP (polypropylene) film with high transparency and clarity.

The downward extrusion machine produces high quality PP film rolls suitable for the textile and garment industry, food packaging, stationery products, flower packaging, zipper bags and other transparent packaging bags.

The water cooling system ensures the transparency of the final film product.

The standard machine includes 3 sets of different sized water rings for flexible production of different sized final film products. The special air ring design ensures the stability of the PP bubble during the production process.

参数及规格 PARAMETERS**Main Technical Parameter**

Model 型号	TW-PP55	TW-PP65	TW-PP75
Max. width 最大膜宽	100-600mm	200-800mm	300-1000mm
Raw Material 使用材料	PP		
Thickness 薄膜厚度	0.01-0.15MM		
Screw dia. 螺杆直径	Φ55	Φ65	Φ75
Max. Capacity 最大产量	45kg/hr	50kg/hr	60kg/hr
Main Motor Power 电机功率	15kw	22kw	30kw
Gear-box 齿轮箱	146	173	180
Die head type 膜头类型	ONE LAYER EXTRUDING		
Water ring 水环	3sets	3sets	3sets
Machine Weight 设备重量	2500kg	2800kg	3500kg

0
1

NAME: ZIPLOCK PE FILM BLOWING MACHINE



Use: Zip lock bag is a press-fit resalable packaging bag. It is an environmentally friendly product, tough and durable, reusable, can be printed on the surface of advertising, mark, can be used as a refrigerator fresh bag, long service life. Many clothing and food brands have used self-sealing bags to package their products, which can prevent things from falling apart, play a summarising role, give consumers a neat and standard image, popular with consumers. And can also be reused, a gentle press of the self-sealing bags will be sealed tight, non-toxic and tasteless, good flexibility, sealing arbitrary, very convenient.

Raw materials of this machine should be selected LDPE, index in 4.5-5.5, widely applying to high grade packing of food, sugar, medicine, jewelry, clothing, metal fittings, documents, directions, files and etc., The market potentiality is great.

参数及规格 PARAMETERS

Main Technical Parameter		
Model 型号	TW-ZP50	TW-ZP55
Max. width 最大膜宽	100-400mm	100-500mm
Raw Material 使用材料	LDPE	
Thickness 薄膜厚度	0.01-0.15MM	
Screw dia. 螺杆直径	Φ50	Φ55
Max. Capacity 最大产量	10-15kg/hr	15-20kg/hr
Main Motor Power 电机功率	5.5kw	7.5kw
Gear-box 齿轮箱	133	133
Colorful zipper 拉链颜色	color injector option	
Machine Weight 设备重量	2000kg	2500kg